

eSMART⁴BUILDING

DESIGNED FOR BUDGET HOME CONTROL



JMobile inside

EXOR

- Flexible control of building for today and tomorrow
- Control of lights, blinds, temperature, heating, etc.
- Scene programming for a more comfortable life
- Ready for wall mounting
- Display Size 4.3", 7" and 10.1"
- Resistive Touchscreen
- Brilliant Display with LED Backlight
- Programmable with JMobile Studio
- Ethernet, USB and Serial Port
- Lightweight and low-power design
- Support of building automation protocols
- BACnet IP and MS/TP, KNX IP
- CE, cULus approval

eSMART⁴BUILDING

DESIGNED FOR BUDGET HOME CONTROL



	eSMART04	eSMART07M	eSMART10
Display	4.3" TFT 16:9	7" TFT 16:9	10.1" TFT 16:9
Resolution	480x272	800x480	1024x600
Backlight	LED	LED	LED
Brightness	200 Cd/m ² typ	200 Cd/m ² typ	200 Cd/m ² typ
Dimming	Yes	Yes	Yes
Colors	64K	64K	64K
Touchscreen	Resistive	Resistive	Resistive
Portrait Mode	Yes	Yes	Yes
CPU	ARM CORTEX-A8 - 300 MHz	ARM Cortex A8 1GHz	ARM Cortex A8 1GHz
RAM	256 MB	512 MB	512 MB
Flash	2 GB	4 GB	4 GB
Application Memory	30 MB	60 MB	60 MB
Serial	RS-232, RS-485, RS-422, software configurable	RS-232, RS-485, RS-422, software configurable	RS-232, RS-485, RS-422, software configurable
Ethernet	10/100 Mbit	10/100 Mbit	10/100 Mbit
USB	1x Host (V2.0, max. 500 mA)	1x Host (V2.0, max. 500 mA)	1x Host (V2.0, max. 500 mA)
RTC	Supercapacitor	Supercapacitor	Supercapacitor
Power Supply	24 Vdc (18 to 32 Vdc)	24 Vdc (18 to 32 Vdc)	24 Vdc (18 to 32 Vdc)
Current Consumption	0.25 A max. at 24Vdc	0.3 A at 24Vdc (max.)	0.38 A at 24Vdc(max.)
Operating Temperature	0 to 50 °C	0 to 50 °C	0 to 50 °C
Storage Temperature	-20 to +70 °C	-20 to +70 °C	-20 to +70 °C
Operating and storage humidity	5 - 85%, RH non condensing	5 - 85%, RH non condensing	5 - 85%, RH non condensing
Weight	Approx 0.4 Kg	Approx 0.6 Kg	Approx 1.0 Kg
Faceplate (LxH)	147x107 mm	187x147 mm	282x197 mm
Cutout (AxB)	136x96 mm	176x136 mm	271x186 mm
Depth (D+T)	29 + 5 mm	29 + 5 mm	29 + 5 mm
Protection Class (front)	IP66, Type 2 and 4X	IP66, Type 2 and 4X	IP66, Type 2 and 4X
Protection Class (rear)	IP20	IP20	IP20
Approvals	CE, cULus	CE, cULus	CE, cULus



R-BOX15



R-BOX16



R-BOX17